

FORM PTO-1390 (Modified)
(REV 11-98)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

112740-217

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

09/856919

INTERNATIONAL APPLICATION NO.
PCT/DE99/03613INTERNATIONAL FILING DATE
12 November 1999PRIORITY DATE CLAIMED
26 November 1998

TITLE OF INVENTION

METHOD FOR ALIGNING PACKET LOSS PRIORITY INFORMATION IN A DATA-PACKET-SWITCHING
COMMUNICATIONS DEVICE

APPLICANT(S) FOR DO/EO/US

Herbert Heiss et al.

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c) (2))
 - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ A copy of the International Search Report (PCT/ISA/210).
8. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
9. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
10. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).
11. ☒ A copy of the International Preliminary Examination Report (PCT/IPEA/409).
12. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).

Items 13 to 20 below concern document(s) or information included:

13. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
14. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
15. ☒ A **FIRST** preliminary amendment.
16. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
17. ☒ A substitute specification.
18. ☐ A change of power of attorney and/or address letter.
19. ☒ Certificate of Mailing by Express Mail
20. ☒ Other items or information:

Submission of Drawings - Figure1 on one sheet

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 09/856919)	INTERNATIONAL APPLICATION NO. PCT/DE99/03613	ATTORNEY'S DOCKET NUMBER 112740-217
--	--	---

21. The following fees are submitted:				CALCULATIONS PTO USE ONLY	
BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :					
<input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO				\$1,000.00	
<input checked="" type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO				\$860.00	
<input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO				\$710.00	
<input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4)				\$690.00	
<input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4)				\$100.00	
ENTER APPROPRIATE BASIC FEE AMOUNT =				\$860.00	
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).				\$0.00	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	7 - 20 =	0	x \$18.00	\$0.00	
Independent claims	1 - 3 =	0	x \$80.00	\$0.00	
Multiple Dependent Claims (check if applicable). <input type="checkbox"/>				\$0.00	
TOTAL OF ABOVE CALCULATIONS =				\$860.00	
Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28) (check if applicable). <input type="checkbox"/>				\$0.00	
SUBTOTAL =				\$860.00	
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).				\$0.00	
TOTAL NATIONAL FEE =				\$860.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). <input type="checkbox"/>				\$0.00	
TOTAL FEES ENCLOSED =				\$860.00	
				Amount to be refunded	\$
				charged	\$

- ☒ A check in the amount of **\$860.00** to cover the above fees is enclosed.
- ☐ Please charge my Deposit Account No. _____ in the amount of _____ to cover the above fees.
A duplicate copy of this sheet is enclosed.
- ☒ The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. **02-1818** A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

William E. Vaughan (Reg. No. 39,056)
Bell, Boyd & Lloyd LLC
P.O. Box 1135
Chicago, Illinois 60690


SIGNATURE

William E. Vaughan

NAME

39, 056

REGISTRATION NUMBER

May 29, 2001

DATE

BOX PCT

IN THE UNITED STATES ELECTED/DESIGNATED OFFICE
OF THE UNITED STATES PATENT AND TRADEMARK OFFICE
UNDER THE PATENT COOPERATION TREATY-CHAPTER II

5

PRELIMINARY AMENDMENT

APPLICANTS: Herbert Heiss et al. DOCKET NO: 112740-217
SERIAL NO: GROUP ART UNIT:
EXAMINER:
INTERNATIONAL APPLICATION NO: PCT/DE99/03613
INTERNATIONAL FILING DATE: 12 November 1999
INVENTION: METHOD FOR ALIGNING PACKET LOSS PRIORITY
INFORMATION IN A DATA-PACKET-SWITCHING
COMMUNICATIONS DEVICE

10

15

Assistant Commissioner for Patents,
Washington, D.C. 20231

20

Sir:
Please amend the above-identified International Application before entry into
the National stage before the U.S. Patent and Trademark Office under 35 U.S.C. §371
as follows:

In the Specification:

25

Please replace the Specification of the present application, including the
Abstract, with the following Substitute Specification:

S P E C I F I C A T I O N**TITLE**

**METHOD FOR ALIGNING PACKET LOSS PRIORITY INFORMATION
IN A DATA-PACKET-SWITCHING COMMUNICATIONS DEVICE**

BACKGROUND OF THE INVENTION**Field of the Invention**

The present invention relates, generally, to a method for aligning packet loss
priority information in a data-packet-switching communications device and, more

T06250-6T69550

specifically, to such a method wherein the packet loss priority information may be modified depending on a connection type or an application-specific data traffic type and the original packet loss priority information is restored after a data packet has been switched in a respective communications device.

5 **Description of the Prior Art**

10 In existing and future packet-oriented communications networks, different monitoring strategies are and will be provided to monitor variable and defined data packet transmission rates. Particularly in communications networks operated on a cell-oriented basis, for example ATM communications networks operating
15 according to the Asynchronous Transfer Mode, loss priorities are allocated to ATM cells which are to be transmitted and, with reference to the loss priorities, a decision is made in a communications device concerning the further switching of the respective data packet. On the basis of the allocated loss priorities, a decision is made in the respective communications device with the aid of a monitoring
20 procedure; in particular, concerning the further switching or rejection of an ATM cell. The data packets which can be rejected within the ATM communications network in the event of overload without the loss of real-time-related, connection-individual information, thus can be defined via the packet-individual allocation of loss priorities.

25 Furthermore, different traffic classes or connection types are defined in the proposal entitled "Traffic Management 4.0" of the ATM Forum 1996. These include Constant Bit Rate (CBR) connections, Variable Bit Rate (VBR) connections, Available Bit Rate (ABR) connections and Unspecified Bit Rate (UBR) connections. The Constant Bit Rate connection type is used for virtual
30 connections, for which a defined transmission bandwidth must be continuously provided for the duration of the virtual connection. The Constant Bit Rate connection type is therefore used, in particular, for real-time-related, virtual applications such as voice transmission.

35 The Variable Bit Rate connection type is defined for virtual connections with variable or changing transmission requirements in the proposal entitled "Traffic Management 4.0" of the ATM Forum 1996. Knowledge of the traffic characteristics of the application represented by the respective virtual connection is advantageous for this purpose. A distinction is made, in particular, between real-time-related and non-real-time-related Variable Bit Rate connections wherein, for
40 example, transmission of real-time-related video data with a variable bandwidth is to be understood as a real-time-related Variable Bit Rate connection.

The Available Bit Rate connection type enables applications to which no special transmission bandwidth is allocated. The applications can use the transmission bandwidth which is currently possible in the ATM communications network, wherein a maximum and a minimum transmission rate are allocated, in each case, to the respective Available Bit Rate connection and these limit values must not be exceeded or undershot. On the basis of the usage factor of the respective ATM communications device, the currently possible transmission rate is indicated to the transmission device with the aid of control cells periodically inserted into the ATM cell stream. With the aid thereof, following the arrival of the control cells in the transmission device, the transmission rate of the ATM cells of the respective virtual connection is adapted to the currently possible transmission rate. In the case of the Unspecified Bit Rate connection type, no defined cell loss information or cell delay times are allocated to the respective virtual connection. Instead, the Unspecified Bit Rate connection type represents a "best-effort" service class which is provided in practice, for example, for Internet applications.

The loss priorities allocated to the respective ATM cells of a virtual connection, i.e. the cell loss priority information transmitted in an external data packet header with the data packet, are evaluated during the switching of the individual virtual connections within an ATM communications device, depending on the connection type. The connection type of the respective ATM cell is thus initially defined and, following alignment of the connection type priority with the loss priority of the respective ATM cell, a decision is made with the aid of the monitoring procedure concerning the forwarding or rejection of the ATM cell. The data packets are then further processed or switched in the ATM communications device with the aid of the switching elements, inter alia on the basis of the cell loss priority information recorded in the external data packet header.

Two connection types, the Constant Data Rate connection type and connections with a low loss priority, have primarily been taken into account in known and practically relevant methods for aligning cell loss priority information. According to the definition of the aforementioned connection classes by the proposal entitled "Traffic Management Specification 4.0" of the ATM Forum, the newly added connection classes must be taken into account in existing data-packet-switching communications devices and the loss priorities which differ according to the connection type must therefore be aligned with the existing communications devices; i.e., in particular with their switching networks. In the known methods, particularly those relating to Constant Bit Rate connections, a check is carried out

by the communications device or its switching elements on the cell loss priority information, wherein a low loss priority is allocated as standard to Constant Bit Rate connections so that these connections are never rejected in the event of overload. In contrast to this, in the case of virtual connections with a high loss
5 priority, for example Variable Bit Rate connections, the associated ATM cells are rejected within the communications device in the event of overload.

An object of the present invention, therefore, is to improve the alignment of packet loss priority information for overload control of a data-packet-switching communications device.

10

SUMMARY OF THE INVENTION

Thus, according to the present invention, the packet loss priority information is read from the incoming data packets. The packet loss priority information of the buffered data packet is then modified depending on the connection type or application-specific data traffic type and the originally stored
15 packet loss priority information is restored after a data packet has been switched in the communications device in the respective data packet. With the aid of the method according to the present invention, the connection type or application-specific data traffic type is advantageously defined during the set-up of a virtual connection within the communications device and, if necessary, i.e. depending on
20 the connection type or application-specific data traffic type, the packet loss priority information is modified. The existing switching elements may continue to be used unchanged via this modification, prior to the switching of data packets, of the loss priorities depending on the connection-specific or application-specific data traffic type.

25 According to another embodiment of the method of the present invention, packet loss priority information read from the buffered data packet is recorded in an additional, communications-device-specific data packet header. The additional data packet header is then attached to the buffered data packet and the buffered data packet, including the attached, additional data packet header, is switched in the
30 communications device. This ensures that, with the aid of the additional data packet header provided for switching within the communications device, also known in the technical field as an "internal" header, the original packet loss priority information is particularly advantageously transferred to the output unit of the communications device. Ineffective buffering of the original packet loss priority
35 information in a further memory area and its separate transfer, for example with the

aid of the control unit, to the output unit, in which the latter is re-inserted into the data packet, is thereby avoided.

According to a further advantageous embodiment of the present method different loss priorities are allocated by the packet loss priority information to the
5 respective data packet. The allocation of different loss priorities with the aid of the packet loss priority information is based on the proposal entitled "Traffic Management Specification 4.0" of the ATM Forum 1996.

A further advantage of the method according to the present invention is that the
10 respective data packets of a group of data packets are modified with packet loss priority information depending on the connection type or application-specific data traffic type. Thus, for example, in a Variable Bit Rate connection, a number of data packets of the virtual connection can be combined into groups, wherein the packet loss priority information of the data packets of the relevant group can be modified independently of a further group of the virtual connection. This makes the
15 prioritization options which are available within the communications device more flexible for a virtual connection and, in order to define the packet loss priority information of a group, it suffices to define the packet loss priority information of one data packet of the group. Consequently, the further data packets of the group can be further processed without checking the packet loss priority information as with the
20 checked data packet. The definition of the packet loss priority information of the further data packets of a group is thus avoided, thereby dynamically reducing the load imposed on available computer resources.

According to a further embodiment of the present invention, after a data
packet has been switched in the communications device, the additional
25 communications-device-specific data packet header attached to the data packet is removed. Thus, after each data packet has been switched, the data packet, including the original packet loss priority information, is advantageously forwarded by the communications device to the communications network.

In cell-switching communications devices, the packet loss priority
30 information is advantageously defined by cell loss priority information. The allocation of cell loss priority information in cell-switching communications devices, particularly those operating according to the Asynchronous Transfer Mode, is based on the proposal entitled "Traffic Management Specification Version 4.0" of the ATM Forum 1996. According to this proposal, information which
35 includes one bit, the "Cell Loss Priority" bit, is provided in each ATM cell for the allocation of cell loss priority information.

Additional features and advantages of the present invention are described in, and will be apparent from, the Detailed Description of the Preferred Embodiments and the Drawings.

DESCRIPTION OF THE DRAWINGS

Figure 1 shows a block diagram schematic of an ATM communications device to which the method of the present invention is directed.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the block diagram according to Figure 1, an ATM communications device ATM-KE operating according to the Asynchronous Transfer Mode is shown schematically, to which a multiplicity of offering lines E1 to En and a multiplicity of serving lines A1 to An are connected with the aid of connection units AE. Of these, the offering lines E1 to En, the serving lines A1 to An, and one of a number of possible connection units AE are shown as examples in Figure 1. Via the offering lines E1 to En and the serving lines A1 to An, ATM cells are transmitted via virtual connections according to the Asynchronous Transfer Mode, wherein variable or defined transmission rates are provided for the transmission of the ATM cells of virtual connections. In the block diagram, a virtual connection Vx is shown as an example by a broken line with its offering line Ex and its serving line Ax. As shown in Figure 1, the connection unit AE has a number of processing devices BHE, one processing device BHE being allocated in each case to each of the offering lines E1 to En and to the serving lines A1 to An. To explain the method according to the present invention, the offering and serving processing devices BHEE/BHEA allocated to the virtual connection Vx are shown in the block diagram as examples, the offering processing device BHEE being connected to the serving line Ex and the serving processing device BHEA being connected to the serving line Ax. The ATM cells DPx transmitted in the virtual connection Vx are supplied to the offering processing device BHEE of the connection units AE. The ATM cells DPx of the virtual connection Vx are then forwarded to a switching arrangement KA of the ATM communications device ATM-KE, a multi-stage structure with a number of interconnecting switching matrices KV being shown as an example in Figure 1 for the switching arrangement KA. However, any single-stage or multi-stage switching arrangements may be provided. The ATM cells DPx of the virtual connection Vx are then forwarded by the serving processing device BHEA from the switching arrangement KA to the serving line Ax.

The processing devices BHE/BHEE/BHEA are equipped with a memory unit PS and a microcontroller MC, the memory unit PS and the microcontroller MC

of the offering and serving processing devices BHEE/BHEA being shown in Figure 1 as examples. On arrival of an ATM cell DPx of the virtual connection Vx in the ATM communications device ATM-KE, the ATM cell DPx is forwarded to the serving handling device BHEE of the connection unit AE, where it is buffered in the memory unit PS. The packet loss priority information CLPx transferred in the buffered ATM cell DPx is read from the ATM cell DPx with the aid of the microcontroller MC and is recorded in an additional, communications-device-specific data packet header DKx. The modified packet loss priority information CLPmx is defined for the respective connection type for the ATM communications device ATM-KE and is stored in a table; for example, a low loss priority is always provided for a Constant Bit Rate connection. The modified packet loss priority information provided for the respective connection type is then recorded in the ATM cell DPx or stored in the memory unit PS instead of the packet loss priority information CLPx, depending on the connection type of the virtual connection Vx. In addition, the additional data packet header DKx containing, inter alia, the original packet loss priority information CLPx is attached by the microcontroller MC to the ATM cell DPx. The ATM cell DPx, including the attached additional data packet header DKx, is then transferred to the switching arrangement KA, where it is switched with the aid of the switching matrices KV.

Via the switching information indicated in the additional data packet header DKx, the respective ATM cell DPx, including the attached additional data packet header DKx, is switched to the serving processing device BHEA which is connected to the serving line Ax, where it is buffered in the memory unit PS. The original packet loss priority information CLPx is read by the microcontroller MC during a read cycle from the buffered, additional data packet header DKx attached to the ATM cell DPx and is recorded in the associated ATM cell DPx instead of the modified packet loss priority information CLPmx. The additional data packet header DKx attached to the ATM cell DPx is then removed and the ATM cell DPx is forwarded by the serving processing device BHEA to the serving line Ax.

The application of the method according to the present invention is not restricted to ATM communications devices ATM-KE, but can be used in all communications devices that switch data packets DPx in which packet loss priority information CLPx allocated to the data packets DPx is transferred with the data packets DPx.

Indeed, although the present invention has been described with reference to specific embodiments, those of skill in the art will recognize that changes may be

made thereto without departing from the spirit and scope of the invention as set forth in the hereafter appended claims.

ABSTRACT OF THE DISCLOSURE

5 A method for aligning packet loss priority information for overload control of a data-packet-switching communications device wherein data packets and respectively allocated packet loss priority information are transmitted to the communications device and buffered in relation to a specific connection. The packet loss priority information is then read from the buffered data packets and modified according to the connection type or the application-specific data traffic
10 type. After the data packet has been switched in the communications device, the original packet loss priority information which was switched with the data packets is re-inserted into the corresponding data packet.

In the claims:

15 On page 10, cancel line 1, and substitute the following left-hand justified heading therefor:

We Claim as Our Invention:

Please cancel claims 1-7, without prejudice, and substitute the following claims therefor:

20 8. A method for aligning packet loss priority information for overload control of a communications device that switches data packets, the method comprising the steps of:

transferring and buffering in a memory area, via the communications device, the data packets and respectively allocated loss priority information in relation to a specific connection;

25 reading the packet loss priority information from the buffered data packets; modifying the packet loss priority information of the buffered data packet depending on at least one of the connection type and application-specific data traffic type; and

30 restoring, after a data packet has been switched in the communications device, the original packet loss priority information in the corresponding data packet.

9. A method for aligning packet loss priority information for overload control of a communications device as claimed in claim 8, the method further
35 comprising the steps of:

recording the packet loss priority information read from the buffered data packet in an additional communications-device-specific data packet header;
attaching the additional data packet header to the buffered data packet; and
switching the buffered data packet, including the attached additional data
5 packet header, in the communications device.

10. A method for aligning packet loss priority information for overload control of a communications device as claimed in claim 8, the method further comprising the step of:

10 allocating different loss priorities to the respective data packet by the packet loss priority information.

11. A method for aligning packet loss priority information for overload control of a communications device as claimed in claim 8, the method further
15 comprising the step of:

modifying the respective data packets of a group of data packets with packet loss priority information depending on at least one of the connection type and the application-specific data traffic type.

12. A method for aligning packet loss priority information for overload control of a communications device as claimed in claim 9, the method further comprising the step of:

removing the additional communications-device-specific data packet header attached to the data packet after a data packet has been switched in the
25 communications device.

13. A method for aligning packet loss priority information for overload control of a communications device as claimed in claim 8, wherein, in cell-switching communications devices, the packet loss priority information is cell loss
30 priority information.

14. A method for aligning packet loss priority information for overload control of a communications device as claimed in claim 13, wherein the cell loss priority information is formed from information having one bit.

REMARKS

The present amendment makes editorial changes and corrects typographical errors in the specification, which includes the Abstract, in order to conform the specification to the requirements of United States Patent Practice. No new matter is added thereby. Attached hereto is a marked-up version of the changes made to the specification by the present amendment. The attached page is captioned "**Version With Markings To Show Changes Made**".

In addition, the present amendment cancels original claims 1-7 in favor of new claims 8-14. Claims 8-14 have been presented solely because the revisions by red-lining and underlining which would have been necessary in claims 1-7 in order to present those claims in accordance with preferred United States Patent Practice would have been too extensive, and thus would have been too burdensome. The present amendment is intended for clarification purposes only and not for substantial reasons related to patentability pursuant to 35 USC §§103, 102, 103 or 112. Indeed, the cancellation of claims 1-7 does not constitute an intent on the part of the Applicants to surrender any of the subject matter of claims 1-7.

Early consideration on the merits is respectfully requested.

Respectfully submitted,


(Reg. No. 39,056)

William E. Vaughan
Bell, Boyd & Lloyd LLC
P.O. Box 1135
Chicago, Illinois 60690-1135
(312) 807-4292
Attorneys for Applicants

VERSIONS WITH MARKINGS TO SHOW CHANGES MADE

In The Specification:

The Specification of the present application, including the Abstract, has been amended as follows:

SPECIFICATION

TITLE

5 **Method for aligning packet loss priority information in a data packet-switching communications device**

**METHOD FOR ALIGNING PACKET LOSS PRIORITY INFORMATION
IN A DATA-PACKET-SWITCHING COMMUNICATIONS DEVICE**

BACKGROUND OF THE INVENTION

10 **Description**

Field of the Invention

The present invention relates, generally, to a method for aligning packet loss priority information in a data-packet-switching communications device and, more specifically, to such a method wherein the packet loss priority information may be modified depending on a connection type or an application-specific data traffic type and the original packet loss priority information is restored after a data packet has been switched in a respective communications device.

Description of the Prior Art

In existing and future packet-oriented communications networks, different monitoring strategies are and will be provided to monitor variable and defined data packet transmission rates. Particularly in communications networks operated on a cell-oriented basis, for example ATM communications networks operating according to the Asynchronous Transfer Mode, loss priorities are allocated to ATM cells which are to be transmitted and, with reference to the loss priorities, a decision is made in a communications device, ~~inter alia~~ concerning the further switching of the respective data packet. On the basis of the allocated loss priorities, a decision is made in the respective communications device with the aid of a monitoring procedure; in particular, concerning the further switching or rejection of an ATM cell. The data packets which can be rejected within the ATM communications network in the event of overload without the loss of real-time-related, connection-

09/856919 05301
T05301 67695860

individual information, ~~can thus can~~ be defined ~~by means of~~ via the packet-individual allocation of loss priorities.

Furthermore, different traffic classes or connection types are defined in the proposal entitled "Traffic Management 4.0" of the ATM Forum 1996. These
5 include Constant Bit Rate (CBR) connections, Variable Bit Rate (VBR) connections, Available Bit Rate (ABR) connections and Unspecified Bit Rate (UBR) connections. The Constant Bit Rate connection type is used for virtual connections, for which a defined transmission bandwidth must be continuously provided for the duration of the virtual connection. The Constant Bit Rate
10 connection type is therefore used, in particular, for real-time-related, virtual applications such as voice transmission.

The Variable Bit Rate connection type is defined for virtual connections with variable or changing transmission requirements in the proposal entitled "Traffic Management 4.0" of the ATM Forum 1996. Knowledge of the traffic
15 characteristics of the application represented by the respective virtual connection is advantageous for this purpose. A distinction is made, in particular, between real-time-related and non-real-time-related Variable Bit Rate connections, wherein, for example, transmission of real-time-related video data with a variable bandwidth is to be understood as a real-time-related Variable Bit Rate connection.

20 The Available Bit Rate connection type enables applications to which no special transmission bandwidth is allocated. The applications can use the transmission bandwidth which is currently possible in the ATM communications network, wherein a maximum and a minimum transmission rate are allocated, in each case, to the respective Available Bit Rate connection and these limit values must not be
25 exceeded or undershot. On the basis of the usage factor of the respective ATM communications device, the currently possible transmission rate is indicated to the transmission device with the aid of control cells periodically inserted into the ATM cell stream. With the aid thereof, following the arrival of the control cells in the transmission device, the transmission rate of the ATM cells of the respective virtual
30 connection is adapted to the currently possible transmission rate. In the case of the Unspecified Bit Rate connection type, no defined cell loss information or cell delay times are allocated to the respective virtual connection. Instead, the Unspecified Bit Rate connection type represents a "best-effort" service class, which is provided in practice, for example, for Internet applications.

0955919-059901
T06350-6F695860

The loss priorities allocated to the respective ATM cells of a virtual connection, i.e. the cell loss priority information transmitted in an external data packet header with the data packet, are evaluated during the switching of the individual virtual connections within an ATM communications device, depending on the connection type. The connection type of the respective ATM cell is thus initially defined and, following alignment of the connection type priority with the loss priority of the respective ATM cell, a decision is made with the aid of the monitoring procedure concerning the forwarding or rejection of the ATM cell. The data packets are then further processed or switched in the ATM communications device with the aid of the switching elements, inter alia on the basis of the cell loss priority information recorded in the external data packet header.

Two connection types, - the Constant Data Rate connection type and connections with a low loss priority, - have hitherto primarily been taken into account in known and practically relevant methods for aligning cell loss priority information. According to the definition of the aforementioned connection classes by the proposal entitled "Traffic Management Specification 4.0" of the ATM Forum, the newly added connection classes must be taken into account in existing data-packet-switching communications devices and the loss priorities which differ according to the connection type must therefore be aligned with the existing communications devices; i.e., in particular with their switching networks. In the known methods, particularly those relating to Constant Bit Rate connections, a check is carried out by the communications device or its switching elements on the cell loss priority information, wherein a low loss priority ~~being~~ is allocated as standard to Constant Bit Rate connections so that these connections are never rejected in the event of overload. In contrast to this, in the case of virtual connections with a high loss priority, - for example Variable Bit Rate connections, the associated ATM cells are rejected within the communications device in the event of overload.

~~The underlying~~ An object of the present invention, therefore, is to improve the alignment of packet loss priority information for overload control of a data-packet-switching communications device. ~~The object is achieved on the basis of a method according to the features of the preamble to claim 1 by means of the features of the characterizing part.~~

SUMMARY OF THE INVENTION

~~The essential aspect of the method~~ Thus, according to the present invention, ~~is that~~ the packet loss priority information is read from the incoming data

packets. The packet loss priority information of the buffered data packet is then modified depending on the connection type or application-specific data traffic type and the originally stored packet loss priority information is restored after a data packet has been switched in the communications device in the respective data
5 packet. With the aid of the method according to the present invention, the connection type or application-specific data traffic type is advantageously defined during the set-up of a virtual connection within the communications device and, if necessary, i.e. depending on the connection type or application-specific data traffic type, the packet loss priority information is modified. The existing switching
10 elements may continue to be used unchanged ~~by means of~~ via this modification, prior to the switching of data packets, of the loss priorities depending on the connection-specific or application-specific data traffic type.

According to ~~a further design~~ another embodiment of the method ~~according to~~ of the present invention, packet loss priority information read from the buffered
15 data packet is recorded in an additional, communications-device-specific data packet header. The additional data packet header is then attached to the buffered data packet and the buffered data packet, including the attached, additional data packet header, is switched in the communications device. This ensures that, with the aid of the additional data packet header provided for switching within the
20 communications device, also known in the technical field as an "internal" header, the original packet loss priority information is particularly advantageously transferred to the output unit of the communications device. Ineffective buffering of the original packet loss priority information in a further memory area and its separate transfer, - for example with the aid of the control unit, - to the output unit,
25 in which the latter is re-inserted into the data packet, is thereby avoided.

According to a further advantageous ~~design~~ embodiment of the present method ~~according to the invention~~, different loss priorities are allocated by the packet loss priority information to the respective data packet. The allocation of
30 different loss priorities with the aid of the packet loss priority information is based on the proposal entitled "Traffic Management Specification 4.0" of the ATM Forum 1996.

A further ~~essential~~ advantage of the method according to the present invention is that the respective data packets of a group of data packets are modified with packet loss priority information depending on the connection type or application-specific data
35 traffic type. Thus, for example, in a Variable Bit Rate connection, a ~~plurality~~ number of data packets of the virtual connection can be combined into groups, wherein the

packet loss priority information of the data packets of the relevant group can be modified independently of a further group of the virtual connection. This makes the prioritization options which are available within the communications device more flexible for a virtual connection and, in order to define the packet loss priority information of a group, it suffices to define the packet loss priority information of one data packet of the group. Consequently, the further data packets of the group can be further processed without checking the packet loss priority information as with the checked data packet. The definition of the packet loss priority information of the further data packets of a group is thus avoided, thereby dynamically reducing the load imposed on available computer resources.

According to a further ~~design~~ embodiment of the present invention, after a data packet has been switched in the communications device, the additional communications-device-specific data packet header attached to the data packet is removed. Thus, after each data packet has been switched, the data packet, including the original packet loss priority information, is advantageously forwarded by the communications device to the communications network.

In cell-switching communications devices, the packet loss priority information is advantageously defined by cell loss priority information. The allocation of cell loss priority information in cell-switching communications devices, particularly those operating according to the Asynchronous Transfer Mode, is based on the proposal entitled "Traffic Management Specification Version 4.0" of the ATM Forum 1996. According to this proposal, information ~~comprising~~ which includes one bit, - the "Cell Loss Priority" bit, - is provided in each ATM cell for the allocation of cell loss priority information.

~~The method according to the invention is described in detail below with reference to a block diagram.~~

Additional features and advantages of the present invention are described in, and will be apparent from, the Detailed Description of the Preferred Embodiments and the Drawings.

DESCRIPTION OF THE DRAWINGS

Figure 1 shows a block diagram schematic of an ATM communications device to which the method of the present invention is directed.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the block diagram according to Figure 1, an ATM communications device ATM-KE operating according to the Asynchronous Transfer Mode is shown schematically, to which a multiplicity of offering lines E1 to En and a multiplicity

of serving lines A1 to An are connected with the aid of connection units AE. Of these, the offering lines E1 to En, ~~and the serving lines A1 to An, and also~~ one of a plurality number of possible connection units AE are shown as examples in Figure 1. Via the offering lines E1 to En and the serving lines A1 to An, ATM cells are transmitted via virtual connections according to the Asynchronous Transfer Mode, wherein variable or defined transmission rates ~~being~~ are provided for the transmission of the ATM cells of virtual connections. In the block diagram, a virtual connection Vx is shown as an example by a broken line with its offering line Ex and its serving line Ax. As shown in Figure 1, the connection unit AE has a plurality number of processing devices BHE, one processing device BHE being allocated in each case to each of the offering lines E1 to En and to the serving lines A1 to An. To explain the method according to the present invention, the offering and serving processing devices BHEE/BHEA allocated to the virtual connection Vx are shown in the block diagram as examples, the offering processing device BHEE being connected to the serving line Ex and the serving processing device BHEA being connected to the serving line Ax. The ATM cells DPx transmitted in the virtual connection Vx are supplied to the offering processing device BHEE of the connection units AE. The ATM cells DPx of the virtual connection Vx are then forwarded to a switching arrangement KA of the ATM communications device ATM-KE, a multi-stage structure with a plurality number of interconnecting switching matrices KV being shown as an example in Figure 1 for the switching arrangement KA. However, any single-stage or multi-stage switching arrangements may be provided. The ATM cells DPx of the virtual connection Vx are then forwarded by the serving processing device BHEA from the switching arrangement KA to the serving line Ax.

The processing devices BHE/BHEE/BHEA are equipped with a memory unit PS and a microcontroller MC, the memory unit PS and the microcontroller MC of the offering and serving processing devices BHEE/BHEA being shown in Figure 1 as examples. On arrival of an ATM cell DPx of the virtual connection Vx in the ATM communications device ATM-KE, the ATM cell DPx is forwarded to the serving handling device BHEE of the connection unit AE, where it is buffered in the memory unit PS. The packet loss priority information CLPx transferred in the buffered ATM cell DPx is read from the ATM cell DPx with the aid of the microcontroller MC and is recorded in an additional, communications-device-specific data packet header DKx. The modified packet loss priority information CLPmx is defined for the respective connection type for the ATM communications

device ATM-KE and is stored in a table; - for example, a low loss priority is always provided for a Constant Bit Rate connection. The modified packet loss priority information provided for the respective connection type is then recorded in the ATM cell DPx or stored in the memory unit PS instead of the packet loss priority information CLPx, depending on the connection type of the virtual connection Vx. In addition, the additional data packet header DKx containing, inter alia, the original packet loss priority information CLPx is attached by the microcontroller MC to the ATM cell DPx. The ATM cell DPx, including the attached additional data packet header DKx, is then transferred to the switching arrangement KA, where it is switched with the aid of the switching matrices KV.

~~By means of~~ Via the switching information indicated in the additional data packet header DKx, the respective ATM cell DPx, including the attached additional data packet header DKx, is switched to the serving processing device BHEA which is connected to the serving line Ax, where it is buffered in the memory unit PS. The original packet loss priority information CLPx is read by the microcontroller MC during a read cycle from the buffered, additional data packet header DKx attached to the ATM cell DPx and is recorded in the associated ATM cell DPx instead of the modified packet loss priority information CLPmx. The additional data packet header DKx attached to the ATM cell DPx is then removed and the ATM cell DPx is forwarded by the serving processing device BHEA to the serving line Ax.

The application of the method according to the present invention is not restricted to ATM communications devices ATM-KE, but can be used in all communications devices that switch data packets DPx, in which packet loss priority information CLPx allocated to the data packets DPx is transferred with the data packets DPx.

Indeed, although the present invention has been described with reference to specific embodiments, those of skill in the art will recognize that changes may be made thereto without departing from the spirit and scope of the invention as set forth in the hereafter appended claims.

Abstract

ABSTRACT OF THE DISCLOSURE

~~Method~~ A method for aligning packet loss priority information for overload control of a data-packet-switching communications device wherein ~~Data~~ data packets (~~DPx~~) and respectively allocated packet loss priority information (~~CLPx~~) are transmitted to ~~a~~ the communications device (~~ATM-KE~~) and buffered in relation to a specific connection. The packet loss priority information (~~CLPx~~) is then read from the buffered data packets (~~DPx~~) and modified according to the connection type or the application-specific data traffic type. After the data packet (~~DPx~~) has been switched in the communications device (~~ATM-KE~~), the original packet loss priority information which was switched with the data packets (~~DPx~~) is re-inserted into the corresponding data packet (~~DPx~~).

Description

Method for aligning packet loss priority information in a data-packet-switching communications device

5 In existing and future packet-oriented communications networks, different monitoring strategies are provided to monitor variable and defined data packet transmission rates. Particularly in communications networks operated on a cell-oriented
10 basis, for example ATM communications networks operating according to the Asynchronous Transfer Mode, loss priorities are allocated to ATM cells which are to be transmitted and, with reference to the loss priorities, a decision is made in a communications
15 device, inter alia concerning the further switching of the respective data packet. On the basis of the allocated loss priorities, a decision is made in the respective communications device with the aid of a monitoring procedure in particular concerning the
20 further switching or rejection of an ATM cell. The data packets which can be rejected within the ATM communications network in the event of overload without the loss of real-time-related, connection-individual information can thus be defined by means of the packet-
25 individual allocation of loss priorities.

Furthermore, different traffic classes or connection types are defined in the proposal entitled "Traffic Management 4.0" of the ATM Forum 1996. These include Constant Bit Rate (CBR) connections, Variable
30 Bit Rate (VBR) connections, Available Bit Rate (ABR) connections and Unspecified Bit Rate (UBR) connections. The Constant Bit Rate connection type is used for virtual connections, for which a defined transmission bandwidth must be continuously provided for the
35 duration of the virtual connection. The Constant Bit Rate connection type is therefore used in particular

09856919-052901

for real-time-related, virtual applications such as voice transmission.

5 The Variable Bit Rate connection type is defined for virtual connections with variable or changing transmission requirements in the proposal
entitled "Traffic Management 4.0" of the ATM Forum 1996. Knowledge of the traffic characteristics of the application represented by the respective virtual connection is advantageous for this purpose. A
10 distinction is made in particular between real-time-related and non-real-time-related Variable Bit Rate connections, wherein, for example, transmission of real-time-related video data with a variable bandwidth is to be understood as a real-time-related Variable Bit
15 Rate connection.

The Available Bit Rate connection type enables applications to which no special transmission bandwidth is allocated. The applications can use the transmission bandwidth which is currently possible in the ATM
20 communications network, wherein a maximum and a minimum transmission rate are allocated in each case to the respective Available Bit Rate connection and these limit values must not be exceeded or undershot. On the basis of the usage factor of the respective ATM
25 communications device, the currently possible transmission rate is indicated to the transmission device with the aid of control cells periodically inserted into the ATM cell stream. With the aid thereof, following the arrival of the control cells in
30 the transmission device, the transmission rate of the ATM cells of the respective virtual connection is adapted to the currently possible transmission rate. In the case of the Unspecified Bit Rate connection type, no defined cell loss information or cell delay times
35 are allocated to the respective virtual connection. Instead, the Unspecified Bit Rate connection type represents a "best-effort" service class, which is

0955919.032901
T06550" 6T695560

GR 98 P 5829

provided in practice, for example, for Internet applications.

09050919-052901

The loss priorities allocated to the respective ATM cells of a virtual connection, i.e. the cell loss priority information transmitted in an external data packet header with the data packet, are evaluated during the switching of the individual virtual connections within an ATM communications device, depending on the connection type. The connection type of the respective ATM cell is thus initially defined and, following alignment of the connection type priority with the loss priority of the respective ATM cell, a decision is made with the aid of the monitoring procedure concerning the forwarding or rejection of the ATM cell. The data packets are then further processed or switched in the ATM communications device with the aid of the switching elements, inter alia on the basis of the cell loss priority information recorded in the external data packet header.

Two connection types - the Constant Data Rate connection type and connections with a low loss priority - have hitherto primarily been taken into account in known and practically relevant methods for aligning cell loss priority information. According to the definition of the aforementioned connection classes by the proposal entitled "Traffic Management Specification 4.0" of the ATM Forum, the newly added connection classes must be taken into account in existing data-packet-switching communications devices and the loss priorities which differ according to the connection type must therefore be aligned with the existing communications devices, i.e. in particular with their switching networks. In the known methods, particularly those relating to Constant Bit Rate connections, a check is carried out by the communications device or its switching elements on the cell loss priority information, a low loss priority being allocated as standard to Constant Bit Rate connections so that these connections are never rejected in the event of overload. In contrast to this,

GR 98 P 5829

- 3a -

in the case of virtual connections with a high loss
priority - for example Variable Bit Rate connections -

0906319 03290
0906319 03290

the associated ATM cells are rejected within the communications device in the event of overload.

5 The underlying object of the invention is to improve the alignment of packet loss priority information for overload control of a data-packet-switching communications device. The object is achieved on the basis of a method according to the features of the preamble to claim 1 by means of the features of the characterizing part.

10 The essential aspect of the method according to the invention is that the packet loss priority information is read from the incoming data packets. The packet loss priority information of the buffered data packet is then modified depending on the connection
15 type or application-specific data traffic type and the originally stored packet loss priority information is restored after a data packet has been switched in the communications device in the respective data packet. With the aid of the method according to the invention,
20 the connection type or application-specific data traffic type is advantageously defined during the set-up of a virtual connection within the communications device and, if necessary, i.e. depending on the connection type or application-specific data traffic
25 type, the packet loss priority information is modified. The existing switching elements may continue to be used unchanged by means of this modification, prior to the switching of data packets, of the loss priorities depending on the connection-specific or application-specific data traffic type.
30

According to a further design of the method according to the invention, packet loss priority information read from the buffered data packet is recorded in an additional, communications-device-

09656919-052904

specific data packet header. The additional data packet header is then attached to the buffered data packet and the buffered data packet, including the attached, additional data packet header, is switched in the communications device. This ensures that, with the aid of the additional data packet header provided for switching within the communications device, also known in the technical field as an "internal" header, the original packet loss priority information is particularly advantageously transferred to the output unit of the communications device. Ineffective buffering of the original packet loss priority information in a further memory area and its separate transfer - for example with the aid of the control unit - to the output unit, in which the latter is re-inserted into the data packet, is thereby avoided.

According to a further advantageous design of the method according to the invention, different loss priorities are allocated by the packet loss priority information to the respective data packet. The allocation of different loss priorities with the aid of the packet loss priority information is based on the proposal entitled "Traffic Management Specification 4.0" of the ATM Forum 1996.

A further essential advantage of the method according to the invention is that the respective data packets of a group of data packets are modified with packet loss priority information depending on the connection type or application-specific data traffic type. Thus, for example, in a Variable Bit Rate connection, a plurality of data packets of the virtual connection can be combined into groups, wherein the packet loss priority information of the data packets of the relevant group can be modified independently of a further group of the virtual connection. This makes the prioritization options which are available within the communications device more flexible for a virtual

connection and, in order to define the packet loss priority information of a group, it suffices to define the packet loss priority information of one data packet of the group. Consequently, the further data packets of the group can be further processed without checking the packet loss priority information as with the checked data packet. The definition of the packet loss priority information of the further data packets of a group is thus avoided, thereby dynamically reducing the load imposed on available computer resources.

According to a further design of the invention, after a data packet has been switched in the communications device, the additional communications-device-specific data packet header attached to the data packet is removed. Thus, after each data packet has been switched, the data packet, including the original packet loss priority information is advantageously forwarded by the communications device to the communications network.

In cell-switching communications devices, the packet loss priority information is advantageously defined by cell loss priority information. The allocation of cell loss priority information in cell-switching communications devices, particularly those operating according to the Asynchronous Transfer Mode, is based on the proposal entitled "Traffic Management Specification Version 4.0" of the ATM Forum 1996. According to this proposal, information comprising one bit - the "Cell Loss Priority" bit - is provided in each ATM cell for the allocation of cell loss priority information.

The method according to the invention is described in detail below with reference to a block diagram.

In the block diagram according to Figure 1, an ATM communications device ATM-KE operating according to the Asynchronous Transfer Mode is shown

T06230"6T69860

schematically, to which a multiplicity of offering lines E1 to En and a multiplicity of serving lines A1 to An are connected with the aid of connection units AE. Of these, the offering lines E1 to En and the serving lines A1 to An, and also one of a plurality of possible connection units AE are shown as examples in Figure 1. Via the offering lines E1 to En and the serving lines A1 to An, ATM cells are transmitted via virtual connections according to the Asynchronous Transfer Mode, variable or defined transmission rates being provided for the transmission of the ATM cells of virtual connections. In the block diagram, a virtual connection Vx is shown as an example by a broken line with its offering line Ex and its serving line Ax. As shown in Figure 1, the connection unit AE has a plurality of processing devices BHE, one processing device BHE being allocated in each case to each of the offering lines E1 to En and to the serving lines A1 to An. To explain the method according to the invention, the offering and serving processing devices BHEE/BHEA allocated to the virtual connection Vx are shown in the block diagram as examples, the offering processing device BHEE being connected to the serving line Ex and the serving processing device BHEA being connected to the serving line Ax. The ATM cells DPx transmitted in the virtual connection Vx are supplied to the offering processing device BHEE of the connection units AE. The ATM cells DPx of the virtual connection Vx are then forwarded to a switching arrangement KA of the ATM communications device ATM-KE, a multi-stage structure with a plurality of interconnecting switching matrices KV being shown as an example in Figure 1 for the switching arrangement KA. However, any single-stage or multi-stage switching arrangements may be provided. The ATM cells DPx of the virtual connection Vx are then forwarded by the serving processing device BHEA from the switching arrangement KA to the serving line Ax.

09856919.032901
T0650.6T695860

The processing devices BHE/BHEE/BHEA are equipped with a memory unit PS and a microcontroller MC, the memory unit PS and the microcontroller MC of the offering and serving processing devices BHEE/BHEA being shown in Figure 1 as examples. On arrival of an ATM cell DPx of the virtual connection Vx in the ATM communications device ATM-KE, the ATM cell DPx is forwarded to the serving handling device BHEE of the connection unit AE, where it is buffered in the memory unit PS. The packet loss priority information CLPx transferred in the buffered ATM cell DPx is read from the ATM cell DPx with the aid of the microcontroller MC and is recorded in an additional, communications-device-specific data packet header DKx. The modified packet loss priority information CLPmx is defined for the respective connection type for the ATM communications device ATM-KE and is stored in a table - for example, a low loss priority is always provided for a Constant Bit Rate connection. The modified packet loss priority information provided for the respective connection type is then recorded in the ATM cell DPx or stored in the memory unit PS instead of the packet loss priority information CLPx, depending on the connection type of the virtual connection Vx. In addition, the additional data packet header DKx containing, inter alia, the original packet loss priority information CLPx is attached by the microcontroller MC to the ATM cell DPx. The ATM cell DPx, including the attached additional data packet header DKx, is then transferred to the switching arrangement KA, where it is switched with the aid of the switching matrices KV.

By means of the switching information indicated in the additional data packet header DKx, the respective ATM cell DPx, including the attached additional data packet header DKx, is switched to the serving processing device BHEA which is connected to

T06590" 6T695950

the serving line Ax, where it is buffered in the memory unit PS. The original packet loss priority information CLPx is read by the microcontroller MC during a read cycle from the buffered, additional data packet header DKx attached to the ATM cell DPx and is recorded in the associated ATM cell DPx instead of the modified packet loss priority information CLPmx. The additional data packet header DKx attached to the ATM cell DPx is then removed and the ATM cell DPx is forwarded by the serving processing device BHEA to the serving line Ax.

The application of the method according to the invention is not restricted to ATM communications devices ATM-KE, but can be used in all communications devices that switch data packets DPx, in which packet loss priority information CLPx allocated to the data packets DPx is transferred with the data packets DPx.

T06250" 6T695660

Claims

1. Method for aligning packet loss priority information (CLPx) for overload control of a communications device (ATM-KE) that switches data packets (DPx) to which data packets (DPx) and respectively allocated loss priority information (CLPx) is transferred and buffered in a memory area (PS) in relation to a specific connection,
- 5
- 10 characterized in that
- the packet loss priority information (CLPx) is read from the buffered data packets (DPx),
 - the packet loss priority information (CLPx) of the buffered data packet (DPx) is modified depending on

15 the connection type or application-specific data traffic type,

 - and, after a data packet (DPx) has been switched in the communications device (ATM-KE), the original packet loss priority information (CLPx) is restored

20 in the corresponding data packet (DPx).
2. Method according to claim 1,
- characterized in that
- the packet loss priority information (CLPx) read from the buffered data packet (DPx) is recorded in an
- 25 additional, communications-device-specific data packet header (DKx),
- the additional data packet header (DKx) is then attached to the buffered data packet (DPx) and the buffered data packet (DPx), including the attached,
- 30 additional data packet header (DKx), is switched in the communications device (ATM-KE).
3. Method according to one of claims 1 or 2, characterized in that

00656319.002901

different loss priorities are allocated to the respective data packet (DPx) by the packet loss priority information (CLPx).

4. Method according to one of claims 1 to 3,
5 characterized in that
the respective data packets (DPx) of a group of data packets (DPx) are modified with packet loss priority information (CLPmx) depending on the connection type or application-specific data traffic type.

10 5. Method according to claim 2,
characterized in that,
after a data packet (DPx) has been switched in the communications device (ATM-KE), the additional communications-device-specific data packet header (DKx)
15 attached to the data packet (DPx) is then removed.

6. Method according to one of claims 1 to 5,
characterized in that,
in cell-switching communications devices (ATM-KE), the packet loss priority information (CLPx) is defined by
20 cell loss priority information (CLPx).

7. Method according to claim 6,
characterized in that
cell loss priority information (CLPx) is formed by information comprising one bit.

00559103904
F0559103904

Abstract

Method for aligning packet loss priority
information for overload control of a data-packet-
5 switching communications device

Data packets (DPx) and respectively allocated
packet loss priority information (CLPx) are transmitted
to a communications device (ATM-KE) and buffered in
relation to a specific connection. The packet loss
10 priority information (CLPx) is then read from the
buffered data packets (DPx) and modified according to
the connection type or the application-specific data
traffic type. After the data packet (DPx) has been
switched in the communications device (ATM-KE), the
15 original packet loss priority information which was
switched with the data packets (DPx) is re-inserted
into the corresponding data packet (DPx).

T06250"6T695829

Declaration and Power of Attorney For Patent Application

Erklärung Für Patentanmeldungen Mit Vollmacht

German Language Declaration

Als nachstehend benannter Erfinder erkläre ich hiermit an Eides Statt:

dass mein Wohnsitz, meine Postanschrift, und meine Staatsangehörigkeit den im Nachstehenden nach meinem Namen aufgeführten Angaben entsprechen,

dass ich, nach bestem Wissen der ursprüngliche, erste und alleinige Erfinder (falls nachstehend nur ein Name angegeben ist) oder ein ursprünglicher, erster und Miterfinder (falls nachstehend mehrere Namen aufgeführt sind) des Gegenstandes bin, für den dieser Antrag gestellt wird und für den ein Patent beantragt wird für die Erfindung mit dem Titel:

VERFAHREN ZUM ABSTIMMEN VON PAKETVERLUSTPRIORITAETSINFOR- MATIONEN

deren Beschreibung

(zutreffendes ankreuzen)

☐ hier beigefügt ist.

☒ am 12.11.1999 als

PCT internationale Anmeldung

PCT Anmeldeungsnummer PCT/DE99/03613

eingereicht wurde und am

abgeändert wurde (falls tatsächlich abgeändert).

Ich bestätige hiermit, dass ich den Inhalt der obigen Patentanmeldung einschliesslich der Ansprüche durchgesehen und verstanden habe, die eventuell durch einen Zusatzantrag wie oben erwähnt abgeändert wurde.

Ich erkenne meine Pflicht zur Offenbarung irgendwelcher Informationen, die für die Prüfung der vorliegenden Anmeldung in Einklang mit Absatz 37, Bundesgesetzbuch, Paragraph 1.56(a) von Wichtigkeit sind, an.

Ich beanspruche hiermit ausländische Prioritätsvorteile gemäss Abschnitt 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 119 aller unten angegebenen Auslandsanmeldungen für ein Patent oder eine Erfindersurkunde, und habe auch alle Auslandsanmeldungen für ein Patent oder eine Erfindersurkunde nachstehend gekennzeichnet, die ein Anmeldedatum haben, das vor dem Anmeldedatum der Anmeldung liegt, für die Priorität beansprucht wird.

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

METHOD FOR ALIGNING OF PACKET LOSS PRIORITY INFORMATION

the specification of which

(check one)

☐ is attached hereto.

☒ was filed on 12.11.1999 as

PCT international application

PCT Application No. PCT/DE99/03613

and was amended on

(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

German Language Declaration

Prior foreign applications
Priorität beansprucht

Priority Claimed

19854656.4 DE 26.11.1998
(Number) (Country) (Day Month Year Filed)
(Nummer) (Land) (Tag Monat Jahr eingereicht)

☒ ☐
Yes No
Ja Nein

(Number) (Country) (Day Month Year Filed)
(Nummer) (Land) (Tag Monat Jahr eingereicht)

☐ ☐
Yes No
Ja Nein

(Number) (Country) (Day Month Year Filed)
(Nummer) (Land) (Tag Monat Jahr eingereicht)

☐ ☐
Yes No
Ja Nein

Ich beanspruche hiermit gemäss Absatz 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 120, den Vorzug aller unten aufgeführten Anmeldungen und falls der Gegenstand aus jedem Anspruch dieser Anmeldung nicht in einer früheren amerikanischen Patentanmeldung laut dem ersten Paragraphen des Absatzes 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 122 offenbart ist, erkenne ich gemäss Absatz 37, Bundesgesetzbuch, Paragraph 1.56(a) meine Pflicht zur Offenbarung von Informationen an, die zwischen dem Anmeldedatum der früheren Anmeldung und dem nationalen oder PCT internationalen Anmeldedatum dieser Anmeldung bekannt geworden sind.

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §122, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

PCT/DE99/03613 12.11.1999
(Application Serial No.) (Filing Date D, M, Y)
(Anmeldeseriennummer) (Anmeldedatum T, M, J)

(Status)
(patentiert, anhängig,
aufgegeben)

(Status)
(patented, pending,
abandoned)

(Application Serial No.) (Filing Date D,M,Y)
(Anmeldeseriennummer) (Anmeldedatum T, M; J)

(Status)
(patentiert, anhängig,
aufgeben)

(Status)
(patented, pending,
abandoned)

Ich erkläre hiermit, dass alle von mir in der vorliegenden Erklärung gemachten Angaben nach meinem besten Wissen und Gewissen der vollen Wahrheit entsprechen, und dass ich diese eidesstattliche Erklärung in Kenntnis dessen abgebe, dass wissentlich und vorsätzlich falsche Angaben gemäss Paragraph 1001, Absatz 18 der Zivilprozessordnung der Vereinigten Staaten von Amerika mit Geldstrafe belegt und/oder Gefängnis bestraft werden koennen, und dass derartig wissentlich und vorsätzlich falsche Angaben die Gültigkeit der vorliegenden Patentanmeldung oder eines darauf erteilten Patentes gefährden können.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

106250 6755560

German Language Declaration

VERTRETUNGSVOLLMACHT: Als benannter Erfinder beauftrage ich hiermit den nachstehend benannten Patentanwalt (oder die nachstehend benannten Patentanwälte) und/oder Patent-Agenten mit der Verfolgung der vorliegenden Patentanmeldung sowie mit der Abwicklung aller damit verbundenen Geschäfte vor dem Patent- und Warenzeichenamt: (Name und Registrationsnummer anführen)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Customer No.

And I hereby appoint
(SEE ATTACHED SHEET)

Telefongespräche bitte richten an:
(Name und Telefonnummer)





Direct Telephone Calls to: (name and telephone number)

Ext. _____

Postanschrift:

Send Correspondence to:

Bell, Boyd & Lloyd LLC
70 West Madison Street, Suite 3300 60602-4207 Chicago, Illinois
Telephone: +1 312 372 1121 and Facsimile +1 312 372 2098
or
Customer No.

Voller Name des einzigen oder ursprünglichen Erfinders:		Full name of sole or first inventor:	
Dr. HERBERT HEISS		Dr. HERBERT HEISS	
Unterschrift des Erfinders	Datum	Inventor's signature	Date
	15.5.2001		
Wohnsitz		Residence	
UNTERHACHING, DEUTSCHLAND		UNTERHACHING, GERMANY	
Staatsangehörigkeit		Citizenship	
DE		DE	
Postanschrift		Post Office Address	
BUSSARDSTR.32		BUSSARDSTR.32	
82008 UNTERHACHING		82008 UNTERHACHING	
Voller Name des zweiten Miterfinders (falls zutreffend):		Full name of second joint inventor, if any:	
Dr. PETER RAU		Dr. PETER RAU	
Unterschrift des Erfinders	Datum	Second Inventor's signature	Date
	16.5.2001		
Wohnsitz		Residence	
MUENCHEN, DEUTSCHLAND		MUENCHEN, GERMANY	
Staatsangehörigkeit		Citizenship	
DE		DE	
Postanschrift		Post Office Address	
BAD ISCHLER STR 11		BAD ISCHLER STR 11	
81241 MUENCHEN		81241 MUENCHEN	

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).

Form PTO-FB-240 (8-83)

Holby M. Abern (P47,372), Robert M. Barrett (30,142), Alan L. Barry (30,819), Thomas C. Basso (46,541), Jeffrey H. Canfield (38,404), Robert W. Connors (46,639), Amy J. Gast (41,773), Timothy L. Harney (38,174), Patricia A. Kane (46,446), Michael S. Leonard (37,557), Edward A. Lehman (22,312), Adam H. Masia (35,602), Dante J. Picciano (33,543), Renato L. Smith (45,117), Maurice E. Teixeira (45,646), William E. Vaughan (39,056), Austin Victor (47,154), and all members of the firm of Bell, Boyd & Lloyd LLC.

THE